

Hydropad W/Integrated Side Gutter

Model 2IS789, 8'L X 16'W

Hydropad above ground steel wash rack systems solve SWPPP requirements for vehicle and equipment wash/collection. Design a wash rack for; drive through or drive-in-back-out, overspray containment walls, awnings, remote control stations, various wash water collection and recycling options, vehicle/wheel and undercarriage wash and raised catwalks.


- Modular design to provide any size wash rack required
- Capture wash water and solid wastes
- Promote EPA and SWPPP compliance
- Easy to deploy or re-deploy

Standard

- 2 ton per axle

Options

- 12 ton per axle
- *30 ton per axle
- Pad connection kit
- Side wall; 4' 6' and 8'
- Gutter side wall; 4' 6' and 8'
- Rail wall, 4', 6' and 8'
- Access ramps;
 - 61.25"L X 24" W, rated 2 ton
 - 119"L X 24"W, rated 2 ton
 - 60"L X 24"W, rated 30 ton
 - 112"L X 48"W, rated 30 ton
- Rain tarps
- Sump box and pump for Hydropad fluid discharge
- Drag conveyor for automatic solid removal



Hydropad wash rack; 16' wide X 40' long, drive on back off design. 4' high walls on 3 sides and drag conveyor for automatic solids removal. Example only.....design exactly what you need.

Specifications

Weight Lbs (kg)	2 ton	1731	(785)
	12 ton	2451	(1112)
	30 ton	2730	(1238)

Dimensions Ft (m) 8' (2.44)L X 16' (4.88)W X 10" (.25)H



Specifications 2023

*8' (2.44)L X 14' (4.88)W X 12" (.3)H

Subject to change without notice



Intertek



Certified Systems Available