

Hydroblaster Pressure Washer

5/3000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 5/3000E high-pressure cold water systems provide flow of 5GPM with variable pressure up to 3000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt Fully Hinged Equipment Enclosure Belt Driven Pump Variable Pressure Wand Trigger Gun 15-Degree Nozzle

Optional Features

50-Hz Motor Stainless Steel Covers

Electrical Disconnect Float Tank Automatic Shut Down Timer Remote Station Operation

Trigger Activated Start Pressure Gauge Hour Meter High Pressure Soap/Chemical Injection Select 50' or 100' High Pressure, Non Marking, Discharge Hose

Hose Reel Nozzle Sets Turbo Nozzle

Specifications

Volume - GPM (LPM) Pressure - PSI (BAR) Electric Motor - HP (KW) Dimensions, Inches (cm) Weight, Lbs (kg) 5 (18.9) 3000 (207) 10 (7.46) 32 (81.3) L X 25 (63.5) W X 39 (99) H 445 (202)

| Standard | | | |
|--------------|---------|---------|--|
| Volts (60Hz) | 230V-3P | 460V-3P | |
| Amps (60Hz) | 25 | 13 | |

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote





Copyright Hydro Engineering, Inc. 2024

Subject to change without notice