



Hydroblaster Pressure Washer

2/1500 ES - Electric Motor, Cold Water Pressure Washer

Hydroblaster 2/1500ES high-pressure cold water systems provide flow of 2GPM with variable pressure up to 1500PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation.

Standard Features

208/230 Volt Full Equipment Enclosure System Shut Down Timer Variable Pressure Wand Trigger Gun 15-Degree Nozzle Stackable Design, up to four (4) high

Optional Features

Electrical Disconnect Remote Control Start/Stop Stations Trigger Operated Start/Stop 50 Hz Electrical Pressure Gauge Hour Meter Select 30',50',75' or 100' High Pressure Discharge Hose Hose Reel Nozzle Sets Turbo Nozzle Discharge Soap Injection Inlet Soap Injection w/ Precision Chemical Pump and Flow Meter Breaker (Float) Tank



Specifications

Volume - GPM (LPM) Pressure - PSI (BAR) Electric Motor - HP (KW) Dimensions, Inches (cm) Weight, Lbs (kg) 2 (7.6) 1500 (103) 2 (1.5) 38 (96.5) L X 19 (48.3) W X 21 (53.3) H 330 (150)

Standard		
Volts (60Hz)	230V-1P	208V-1P
Amps (60Hz)	9	10

Compact floor mount stand with forklift slots

) W X 21 (53.3) H

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote





Subject to change without notice Copyright Hydro Engineering, Inc. 2024