



Hydroblaster Pressure Washer

4/2000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 4/2000E high-pressure cold water systems provide flow of 4GPM with variable pressure up to 2000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt Fully Hinged Equipment Enclosure Belt Driven Pump Variable Pressure Wand Trigger Gun 15-Degree Nozzle

Optional Features

50-Hz Motor Stainless Steel Covers Electrical Disconnect Float Tank Automatic Shut Down Timer Remote Station Operation

Trigger Activated Start Pressure Gauge Hour Meter Portability Kit - Casters High Pressure Soap/Chemical Injection Select 50' or 100' High Pressure, Non Marking, Discharge Hose Hose Reel Nozzle Sets Turbo Nozzle

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
Electric Motor - HP (KW)	5 (3.73)
Dimensions, Inches (cm)	32 (81.3) L X 25 (63.5) W X 39 (99) H
Weight, Lbs (kg)	420 (191)
Standard	

Volts (60Hz)	230V-1P	230V-3P	460V-3P	
Amps (60Hz)	25	14	7	



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

