

Hydroblaster Pressure Washer

5/5000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 5/5000E high-pressure cold water systems provide flow of 5GPM with variable pressure up to 5000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Fully Hinged Equipment Enclosure
Belt Driven Pump
Variable Pressure Wand
Trigger Gun
15-Degree Nozzle

Optional Features

50-Hz Motor Stainless Steel Covers Electrical Disconnect Float Tank Automatic Shut Down Timer Remote Station Operation Trigger Activated Start

Pressure Gauge

Hour Meter

High Pressure Soap/Chemical Injection

Select 50' or 100' High Pressure, Non Marking, Discharge Hose

Hose Reel

Nozzle Sets

Turbo Nozzle

Specifications

Volume - GPM (LPM) 5 (18.9) Pressure - PSI (BAR) 5000 (345) Electric Motor - HP (KW) 20 (14.9)

Dimensions, Inches (cm) 32 (81.3) L X 25 (63.5) W X 39 (99) H

Weight, Lbs (kg) 690 (313)

Standard

Volts (60Hz)	230V-3P	460V-3P	
Amps (60Hz)	55	35	



For complete pricing details, Submit a quote online below.

Get a Quote



