

# Hydroblaster Hot Water All Electric Pressure Washer

**Configure the HH-E electric water heater with your choice of E Model Hydroblaster on a common skid with a single power connection.**

HH-E water heaters are available in either 48kW or 72kW input power sizes and are rated up to 3000PSI. At 4GPM with a 50°F inlet water temperature, these are the continuous temperature outputs at

48kW – 126°F
72kW – 168°F

E model Hydroblasters that produce from 3 to 5GPM and 1000 to 3000PSI are certified to UL-1776, CSA, and conform to CE standards.

## Standard HH-E

- 208/230VAC, 3PH, 60Hz, 48kW with E Hydroblaster accommodations
- Single point electrical connection to HH-E and E Hydroblaster
- Skid frame with forklift pockets for combining HH-E water heater and E Hydroblaster

## Options

- 460VAC, 3PH, 60HZ, 48kW
- 460VAC, 3PH, 60HZ, 72kW
- Any of the following E Hydroblasters can be ordered with HH-E water heaters
  - 3/1000E
  - 4/2000E
  - 4/3000E
  - 5/3000E



**Weights and amperage change with E Hydroblaster selection.**

**Main electrical disconnects are not provided and must be configured for both HH-E and E Hydroblaster.**

1. Specifications are effective 2024    2. Specifications are subject to change without notice