

Hydroblaster™

MODEL 65E-CHT (Jetting System for CHT Systems)

NSN 4940-015146978

(Electric Motor or Diesel Engine driven)

PART	65E-CHT	65D-CHT
VOLUME (GPM)	6	6
PRESSURE (PSI)	5000	5000
MOTOR / ENGINE (HP)	20 electric	28 diesel
WEIGHT (LBS)	625	735

Meets UL1776 Standard for Outdoor and Wash Bay Applications



Standard equipment:

- Four-wheel steerable trailer with a tow bar and front wheel brakes
- 300' (in 50' lengths) of high pressure hose (rated at 6250 psi)
- Belt-driven triplex plunger pump. 6 gallons per minute at 5,000 psi
- Full instrumentation- pressure gauge, hour meter, and power off/on switch
- 20 HP electric motor, 460 volt, 3-phase, 60 hertz or 28 hp diesel engine.
- Foot valve for system "no hands" operation during jetting
- Lockable enclosure over pump and motor keeps personnel away from moving parts
- Combination tie downs and lifting rings for easy transport on, off and around the ship
- Hose reel stores 300 ft. of jetting hose for simple access during use in tight quarters
- 16" foam-filled pneumatic tires allows the CHT to move through passageways easily

1. Specifications are effective May 2009 2. Specifications are subject to change without notice.



865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com