Hydroblaster™
Built for the Screen Printer

MODEL	325E	43E
VOLUME (GPM)	3	4
PRESSURE (PSI)	2500	3000
ELECTRIC MOTOR(HP)	5	10
VOLTAGE[1] (STD)	B	(C), D
AMPERAGE	25	28, 14
MOTOR CONTROL	Manual Starter	Magnetic motor starter
WEIGHT (LBS)	210	265
LENGTH (INCHES)	26	32
WIDTH	23	25
HEIGHT	14.5	14.5

Optional Hydroblaster stand adds 6” to overall height

Built to UL1776 Standards for Indoor Applications

Screen Print Line

- Belt drive, General Pump
- Heavy duty electric motor.
- Full equipment cover
- Trigger gun and 36” variable pressure wand
- High pressure nozzle on quick disconnect fitting
- 15’ high pressure hose

[1] Voltage codes: A=115 volt single phase, B=230 volt single phase, C=230 volt three phase, D=460 volt, three phase. Most 230 volt rated systems will operate on 208 volt power supplies.

1. Specifications are effective June 24, 2009 2. Specifications are subject to change without notice.

HE HYDRO ENGINEERING
865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265
HYDROBLASTERS - HYDROKLEEN - HYDROPAD www.hydroblaster.com