

## Hydroblaster™ GHO Series

PART	5/3000	5/5000
VOLUME (GPM)	5.0	5
PRESSURE (PSI)	3000	5000
ENGINE (HP)	18	25
BTU (PER HR X 1000)	440	440
DIMENSIONS	54" wide X 63" long (height depends on options)	
WEIGHT (LBS)	1195	1250

### Standard Features:

- UL1776, CSA & CE Certified
- Heavy channel iron skid frame with forklift slots
- Schedule 80 steel coil
- Belt drive
- Full locking equipment covers
- Trigger gun
- Insulated variable pressure wand
- 15 degree nozzle
- 50' high pressure hose
- Downstream chemical injection



Shown with options

Part#	Description
<b>Temperature Controls</b>	
*1SP592	High Limit Temperature Switch, 225°F
1WQ642	Thermostat, Adjustable
<b>Steam Discharge Options</b>	
*2BG847	No Steam Combo
1YL111	Steam Combo
<b>Engine: Power &amp; Controls</b>	
*1YM125	Kohler 18HP, Electric Start
2BL890	Honda 20HP, Electric Start
1YM126	Kubota Diesel, Water Cooled, Electric Start
<b>Engine: Battery Options</b>	
*1YG062	No Battery
1YG063	Battery, Liquid Acid, Non Shippable
1YG064	Battery, Spiral Cell, Shippable
<b>Coil And Oil Burner Options</b>	
*1YM127	12 Volt DC Burner, Painted, Gas Engine
2BF835	12 Volt DC Burner, Painted, Diesel Engine
1YN131	12 Volt DC Burner, Stainless, Gas Engine
2BF836	12 Volt DC Burner, Stainless, Diesel Engine
1YN133	120 Volt Burner, Painted, Gas Engine
1YM128	120 Volt Burner, Painted, Diesel Engine
2BF833	120 Volt Burner, Stainless, Gas Engine
1YN134	120 Volt Burner, Stainless, Diesel Engine
<b>Gauge &amp; Meter Options</b>	
*2BH851	No Pressure Gauge
2AX753	Pressure Gauge
*1SU640	No Hour Meter
1WR653	Hour Meter
<b>Trim Options</b>	
*1YL112	Painted Housing, Gas Engine
2BF830	Stainless Housing, Gas Engine
1YL114	Painted Housing, Diesel Engine
1YL115	Stainless Housing, Diesel Engine
<b>Discharge Options</b>	
*1SU641	Single High Pressure Nozzle, 15 Degree
1SU642	Four Nozzle Kit, 0,15,25,40 Degree
SU643	Turbo Nozzle
1YN130	Hose Reel Kit

NOTE: \* reflects the standard