

HYDROBLASTER™
5/3000GHOTT/M-ST
NSN 4940-01-358-4247

Self-contained, high-pressure, hot-water washing system with optional diesel engine. Mounted on a four-wheel steerable trailer.



STANDARD FEATURES:

- 525-gallon water tank , two 30-gallon chemical tanks, 12 gallon antifreeze tank
- Key-lockable, stainless steel cover for security, hand brake for rear wheels
- Industrial triplex ceramic high-pressure plunger pump, 5 gpm @ 3000 PSI
- 1 GPM @ 60 PSI 12-volt DC soap pump and soap injector system
- 100 feet of 3/8" high-pressure hose, 100 feet of 1/2" soap delivery hose
- Two trigger gun wands (low-pressure and dual high-pressure)
- 12-volt oversized alternator for all power requirements
- 15, 25 and 40 degree stainless steel nozzles on quick disconnects
- 4-wheel steerable heavy-duty trailer with lifting/tie down rings
- 100 feet of 3/4 " water delivery hose, inlet water filter
- Mounted spare tire & wheel, CO2 fire extinguisher
- 190° F hot water with 440,000 BTU burner
- Redundant safety controls throughout system, full gauge package
- Weight 2250 lbs, dimensions 73" W x 150" L x 72" H
- Key start diesel engine (note: battery not supplied, requires group 26)
- Three hand-crank hose reels
- GSA contract: GS07F-3849A
- UL1776 Certified