

Hydroblaster™

Pneumatic Pressure Washer

NSN 4940-014832063

MODEL	3/1500-P1
VOLUME (GPM)	1 to 3 GPM
PRESSURE (PSI)	100 to 2000 PSI Controlled by inlet air PSI (Water PSI = 20 time inlet air PSI)
WEIGHT (LBS)	75 lbs excluding water/air hoses, detergent and oil
AIR MOTOR (HP) CFM required PSI required	3 up to 50 up to 60-100
MOUNTING & ACCESSORIES	Formed stainless steel base plate mounted, 2 locking casters hose rack, gun holster, 75' air supply hose, 75' water supply hose, 50' high pressure hose, variable pressure wand and nozzle.
LENGTH (INCHES)	18
WIDTH	20
HEIGHT	40

Model 3/1500-P1

- General triplex plunger pump
- Inlet water filter
- Trigger gun with insulated 36" pressure wand
- 50' high pressure hose
- Inlet air regulator, air gauge, lubricator and filter
- Air motor driven with muffler
- 1 gallon soap container



	HE HYDRO <small>ENGINEERING</small>	<p>865 West 2600 South, Salt Lake City, UT 84119 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265</p>	HYDROBLASTERS - HYDROKLEEN - HYDROPAD www.hydroblaster.com
---	---	---	--

1. Specifications are effective March 1, 2000. 2. Specifications are subject to change without notice.