



Hydroblaster Pressure Washer

5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/1500EHOV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 1500PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt

Hinged Access Equipment Enclosure Premium Efficiency Drive Motor Belt Driven Pump Schedule 80 Coil With Extended Warranty Automatic System Shutdown Timer Automatic Burner Ignition and Controls 6 Gallon Front Fill Fuel Oil Tank Low Fuel Level Burner Lockout w/ Indicator Trigger Gun System Discharge Control Dual Nozzle Variable Pressure Wand

Optional Features

Suitable For a Variety of Power Supplies Including 50Hz Lockable Power Disconnect Switch Hour Meter, Pressure and Temperature Gauges Steam (250°F 300PSI) / Hot Water Combination Trigger Actuated Start Remote Control Station In NEMA 4X Enclosures Stainless Trim; Pump Enclosure and Coil Housing Nozzle Options including Turbo Nozzle Discharge Soap/Chemical Injection Precision (Peristaltic Pump) Inlet Soap Soap Injection Flow Meter Plastic Float Tank Fresh/Recycle Water Supply w/Motorized Ball Valve Hose Reels HP Hose, Various Lengths



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181





Hydroblaster Pressure Washer

5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GF	5 (18.	5 (18.9)			
Pressure - P	1500	1500 (103)			
BTU Minimu	44000	440000			
Exhaust Dia	(mm) 8 (203	8 (203.2)			
Electric Moto) 5 (3.7	5 (3.73)			
Dimensions,) 45 (11	45 (114.3) L X 33 (83.8) W X 50 (127) H			
Weight, Lbs	688 (3	688 (312)			
Frame	5BK1	5BK169 (Sm.)			
Coil	18"	18"			
Burner	HD-20	HD-201PC			
SS Trim - He	53 7/8	53 7/8"			
	Standard				
Volts (60Hz)	230V-1P	230V-3P	460V-3P		
Amps (60Hz)	23	14	7		

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

