

Hydroblaster™ Steam Cleaners

(Electric motor driven, oil or gas fired, steam cleaner)

PART #	3/200	4/200
VOLUME (GPM)	3	4
PRESSURE (PSI)	200	200
BTU (PER HR X 1000)	400	560
MAXIMUM TEMPERATURE	300 F.	300 F.
EXHAUST STACK (DIA)	10"	12"
COIL SPEC (SCH80)	1/2"	1/2"
WATER FLOAT TANK (GAL)	2	2
ELECTRIC MOTOR (HP)	1.5	1.5
VOLTAGE CODE* (STD)	A	A
AMPERAGE	16	16
LENGTH (INCHES)	45	51
HEIGHT (W/LEGS)	55	62
WIDTH	34	34
WEIGHT (LBS)	485	640



EHOV-S Oil Fired or EHGVS Gas Fired

- Belt drive, General Pump (Low RPM)
- Full equipment covers
- Auto pilot ignition
- Heavy duty electric motor with reset on all 1 phase
- Float tank
- Flow through gun with insulated variable pressure wand
- 50' hose rated for steam
- Schedule 80 steel coil
- Inlet chemical injection
- Specify fuel type; oil, natural gas, lp gas
- Steam temperatures to 300 degrees F.

*Voltage codes: A=115 volt single phase

Available also in 230 volt single phase, 230 volt three phase, 460 volt three phase. Most 230 volt rated systems will operate on 208 volt power supplies.

1. Specifications are effective January 28, 2003. 2. Specifications are subject to change without notice



865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com