

# E Hydroblaster™

MODEL	4/1000	4/2000	4/3000	5/3000	5/5000
VOLUME (GPM)	4	4	4	5	5
PRESSURE (PSI)	1000	2000	3000	3000	5000
ELECTRIC MOTOR(HP)	3	5	7.5	10	20
VOLTAGE <sup>1</sup> (STD)	(B), C, D	(B), C, D	B,(C), D	(C), D	(C), D
AMPERAGE	16, 8, 4	25, 14, 7	36,28,14	28, 14	55, 35
OVERLOAD	Current sensing, manual reset.				
WEIGHT (LBS)	395	386	428	444	650
LENGTH (INCHES)	45	45	45	45	45
WIDTH	42	42	42	42	42
HEIGHT	48	48	48	48	48

<sup>1</sup> Voltage codes: B=230 volt single phase, C=230 volt three phase, D=460 volt three phase.

## Standard Features:

- Heavy duty electric motor with reset on all 1 phase
- Belt drive
- Full equipment covers
- Trigger gun with insulated variable pressure wand
- 15 degree nozzle
- 50' hose rated 3000 PSI
- Downstream chemical injection

## Choose your options (STD- designates the standard)

### Electrical: Power & Controls

- STD- 208-230V, 1PH, Cam Switch, Stationary  
 OPT- 208-230V, 1PH, Cam Switch, Portable  
 OPT- 208-230V, 1PH, Mag Starter, Stationary  
 OPT-208-230V, 1PH, Mag Starter, Portable  
 OPT- 208-230V, 3PH, Mag Starter, Stationary  
 OPT- 208-230V, 3PH, Mag Starter, Portable  
 OPT- 460V, 3PH, Mag Starter, Stationary  
 OPT-460V, 3PH, Mag Starter, Portable  
 OPT- Shut Down Timer (Requires Magnetic Motor Starter)

### Remote Control Options

- STD- No Remote  
 OPT- Trigger Actuated Start  
 OPT- On/Off Nema 4X Enclosure  
 OPT- On/Off, Explosion Proof

### Hour Meter Option

- STD- No Hour Meter  
 OPT- Hour Meter Opt, 208-230VAC  
 OPT- Hour Meter 24VAC

### Frame Options

- STD-Painted Cover & Panels, 3-15HP  
 OPT- Stainless Cover & Panels, 3-15HP  
 STD-No Casters  
 OPT- Casters



Model E  
Shown with some options

### Discharge Options


- STD- Single High Pressure Nozzle, 15 Degree  
 OPT- Four Nozzle Kit, 0,15,25,40 Degree  
 OPT- Turbo Nozzle, 3500PSI  
 OPT- Hose Reel Kit

### System Gauge Options

- STD- No Pressure Gauge  
 OPT- Pressure Gauge, Pipe Mounted  
 OPT- Temperature Gauge Opt, 4000PSI, 50-550°F

### Inlet Options

- STD- Discharge soap injection  
 OPT- Inlet Soap Injection  
 OPT- Soap Solenoid Control, Remote Switchable  
 STD- No Breaker Tank/Plumbing  
 OPT- Breaker Tank/Plumbing, Plastic Tank  
 OPT- Breaker Tank, SS & Plumbing



865 West 2600 South, Salt Lake City, UT 84119  
 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com