

Hydroblaster™ Single Axle Trailer



Standard Features:

- 3", 4" & 6" channel iron construction
- Heavy duty jack with 2000 lb steel wheel
- Dual safety chains
- Electric or Hydraulic Brakes, both axles
- 12 Volt, D.O.T. approved light package
- These factory engineered trailers integrate both the Hydroblaster pressure washer and water tank into a total system design

Trailer Size Options	
*2DG367	125 Gallon Tank, No Brakes
2DE349	125 Gallon Tank, Electric Brakes
2DG368	225 Gallon Tank, No Brakes
2DF350	225 Gallon Tank, Electric Brakes
2DF351	225 Gallon Tank, Hydraulic Brakes
Trailer Hitch Options	
*2BT974	2" Ball
2DF352	2", Hydraulic Brakes
2BT975	Lunette Eye, Fixed
Trailer Light Options	
*2DG362	Lights, Trailer, 12 Volt
2DG363	Lights, Trailer, 24 Volt
Tire And Wheel Options	
*2BT977	13"
2BT978	15"
2BX014	Spare Tire With Mount, 13"
2BX015	Spare Tire With Mount, 15"
Extension Options	
2DF355	2' Trailer Extension
Trailer Options, 125/225	
2DF357	Pre-spray System, 12 Volt, With 30 Gallon Tank
2DF358	Soap Tank, 30 Gallon, Connected To Discharge Injector
2DF359	Hose Reel, Inlet Water
2DG360	Hose Reel, Pre-spray
Hose Options, Low Pressure	
2BV992	Pre-spray Hose, 1/2", 50 FT.
2BV993	Pre-spray Hose, 1/2", 100FT
2BV994	Inlet Water Hose, 5/8", 50FT.
2BV995	Inlet Water Hose, 5/8", 100FT.

NOTE: * reflects the standard

	865 West 2600 South, Salt Lake City, UT 84119 Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265
	HYDROBLASTERS - HYDROKLEEN - HYDROPAD www.hydroblaster.com

9/5/2006, This specification is subject to change without notice.