

# 2ZV237

## Drive-In Clean Out Tray

The model 2ZV237 Drive-in Tray is a heavy-duty solid settling system. Wash water flows from the Hydropad above ground steel containment wash rack's side gutter into the Drive-in Tray by gravity. Weirs located in the tray quiet the fluid flow which promotes solids settling. Clarified wash water enters the integral sump tank where it is discharged by a pump. When solids accumulate in the bottom of the tray, a skid-steer is used to remove them. Ideal for operations with a lot of heavy soil loads.

### Standard features:

- 6' wide X 12' Long

### Optional features:

- 6' wide X 20' Long Extended Length Tray
- Discharge pump, ½ HP, 120-volt, 1 phase, 60 HZ
- Discharge pump, ½ HP, 220-volt, 1 phase, 50 HZ
- Access Ramps
- Drive-In Tray Splash Guard
- Drive-In Tray Weir



6' wide X 12' long drive in tray shown with optional entry ramps



6' wide X 20' long drive in tray shown with optional entry ramps

### 6' x 12' Drive-In Tray

Dimensions – Ft/Inches (CM) 12' (3658) L x 6'6" (1981) W x 37" (940) H

Weight - LBS (KG) 1808 (820)

### 6' x 20' Drive-In Tray

Dimensions – Ft/Inches (CM) 20' (6096) L x 6'6" (1981) W x 37" (940) H

Weight - LBS (KG) 2768 (1251)

[Get a Quote](#)

### Optional Entry Ramps (2ea)

Add 36" (914cm) to tray length and 230 LBS (230 KG) to overall weight.

1. Specifications are effective 2017. 2. Specifications are subject to change without notice