

Hydrokleen Wastewater Filtration

HE/3000 - Polishing Filtration System

The HE/3000 is designed for flow thru filtration rates up to 12 GPM and incorporates one (1) filtration module. This module incorporates a filtration media that is selected to assist with filtration or recycling requirements. Solids, oils & grease (hydrocarbons) or metals filtration, choose to solve any one (1) filtration requirement with HE/3000. Every Hydrokleen filtration systems that feature PLC operation can also incorporate pH control, bacteria, pathogen and odor elimination and more, along with remote system monitoring. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance.

Standard Features

- Overflow Protection
- Gravity Flow Through Design
- Self-cleaning Tank
- Primary Solids Incline Tank
- Polishing Loop for Fine Solids
- Emulsified Oils, and Hydrocarbon Removal
- PLC Controls

Optional Features

- Remote Operation Monitoring
- [Biological Odor Control and Hydrocarbon Elimination](#)
- Ozone Bacteria Control
- De-foam Control
- [pH Control](#)
- Full System Vented Enclosure



Specifications

Flow Rate - GPM (LPM)	12 (45.4)
Dimensions, Inches (cm)	72" (182.9) L X 36" (91.4) W X 75" (190.5) H
Weight, Lbs (kg)	1006 (456.3)

	Standard
Volts (60Hz)	230V-1P
Amps (60Hz)	11

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)