

# Hydrokleen Wastewater Filtration

## OCS - Oil Coalescing System, Above Ground

The OCS is designed for flow thru filtration rates up to 25 GPM. Our state of the art oil coalescing and skimming systems can be fed by pump or gravity. Emulsified oil and grease are directed through coalescing media where they accumulate on the surface of oil attractant material of the plates. Once large enough to float free to the surface, oils are permanently removed from system by an electric belt skimmer. The automatic skimmer deposits oils into a decanter where trace amounts of water are directed back into the coalescing tank and oils are dispensed into an oil drum or bucket supplied by customer. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance. Hydrokleen filtration / recycling systems are UL-979 and CSA certified, and conform to CE standards.

### Standard Features

- 210 Gallon Tank
- Gravity Flow Through Design
- Self-cleaning Tanks
- Overflow Protection Device
- Oil Coalescing Plate
- Oil Belt Skimmer with Oil / Water Decanter

### Optional Features

- 500 Gallon Tank
- Pressurized Discharge To Drain
- [Biological Odor Control and Hydrocarbon Elimination](#)
- Ozone Bacteria Control
- De-foam Control



### Specifications

Flow Rate - GPM (LPM)	25 (94.6)
Dimensions, Inches (cm)	34.5" (87.6) L X 34.5" (87.6) W X 96" (243.8) H
Weight, Lbs (kg)	550 (249.5)

	Standard
Volts (60Hz)	120V-1P
Amps (60Hz)	0.5

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)