

# Hydroblaster Pressure Washer

## 2/1000 CLOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 2/1000CLOV high-pressure hot water systems provide flow of 2GPM with variable pressure up to 1000PSI. All CLOV systems can be configured for to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. Hydroblaster CLOV system design and quality manufacturing ensures continued performance, reliability and safety. All CLOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and Conform to CE standards.

### Standard Features

- Full Equipment Covers
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- 6 Gallon Fuel Oil Tank
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

### Optional Features

- Supply Voltage
- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Float Tank
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Pressure Gauge
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Nozzle Sets
- [Turbo Nozzle](#)



### Pricing

For complete pricing details,  
Submit a quote online below.

[Get a Quote](#)



# Hydroblaster Pressure Washer

## 2/1000 CLOV - Electric Motor, Hot Water Pressure Washer

### Specifications

Volume - GPM (LPM)	2 (7.6)
Pressure - PSI (BAR)	1000 (69)
BTU Minimum Supply	280,000
Exhaust Diameter - Inch (mm)	8" (203)
Electric Motor - HP (KW)	1.5 (1.1)
Dimensions, Inches (cm)	45" (114.3) L X 26" (66) W X 51" (129.5) H
Weight, Lbs (kg)	490 (222)

	Standard
Volts (60Hz)	120V-1P
Amps (60Hz)	19

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

