

Hydroblaster Pressure Washer

25/500 Demucker - Water Cannon for Equipment Washing

Heavy mud and dirt accumulations can be removed quickly with the Hydroblaster Demucker water cannon. At a rate of 25GPM per minute water is forced through an adjustable nozzle at 500PSI, allowing the operator to use a gentle fan or direct stream against dirt or mud buildup. Dozers, front end loaders, back hoes and other heavy equipment can be cleaned quickly with this system. Our Demucker water cannon employs high efficiency motors that are compatible with various electrical supply voltage for either 60Hz or 50Hz operation. 25/500E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Skid Mounted
- Diaphragm Pump
- 210 Gallon Water Tank
- Trigger Gun
- Variable Spray Pattern Nozzle

Optional Features

- Supply Voltage
- 50-Hz Motor
- Electrical Disconnect
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- Larger Water Storage Capacities



Specifications

Volume - GPM (LPM)	25 (94.6)
Pressure - PSI (BAR)	500 (34.5)
Electric Motor - HP (KW)	20 (14.9)
Dimensions, Inches (cm)	39.5" (100.3) L X 27.5" (69.9) W X 37.75" (95.9) H
Weight, Lbs (kg)	1645 (746)

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	53	27

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)