



# **Hydroblaster Pressure Washer**

### 3/1000 CLGV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 3/1000CLGV high-pressure hot water systems provide flow of 3GPM with variable pressure up to 1000PSI. All CLGV systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. Hydroblaster CLGV system design and quality manufacturing ensures continued performance, reliability and safety. All CLGV model Hydroblaster pressure washers are certified to UL-1776, CSA, and Conform to CE standards.

# **Standard Features**

Full Equipment Covers Belt Driven Pump Schedule 80 Coil Warranty Automatic Ignition Soap/Chemical Injection Exhaust Draft Diverter Variable Pressure Trigger Wand 15-Degree Nozzle Automatic Shutdown Timer



# **Optional Features**

50-Hz Motor Power Vent Stainless Steel Trim Electrical Disconnect Float Tank Remote Station Operation Trigger Activated Start Pressure Gauge Hour Meter Select 50', 75' or 100' High Pressure Discharge Hose Hose Reel Nozzle Sets Turbo Nozzle

## **Specifications**

 Volume - GPM (LPM)
 3 (11.4)

 Pressure - PSI (BAR)
 1000 (69)

 BTU Minimum Supply
 280000

 Exhaust Diameter - Inch (mm) 8 (203.2)
 Electric Motor - HP (KW)
 2 (1.5)

 Dimensions, Inches (cm)
 45 (114.3)
 Weight, Lbs (kg)
 490 (222)

280000 8 (203.2) 2 (1.5) 45 (114.3) L X 26 (66) W X 51 (129.5) H 490 (222)

#### Standard

 Volts (60Hz)
 120V-1P

 Amps (60Hz)
 17.8

Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181



Subject to change without notice

Copyright Hydro Engineering, Inc. 2025

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote