

Hydroblaster Pressure Washer

3/1000 CLOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 3/1000CLOV high-pressure hot water systems provide flow of 3GPM with variable pressure up to 1000PSI. All CLOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. Hydroblaster CLOV system design and quality manufacturing ensures continued performance, reliability and safety. All CLOV model Hydroblaster pressure washers are certified to UL-1776. CSA. and Conform to CE standards.

Standard Features

Full Equipment Covers
Belt Driven Pump
Schedule 80 Coil Warranty
Automatic Ignition
6 Gallon Fuel Oil Tank
Soap/Chemical Injection
Variable Pressure Trigger Wand
15-Degree Nozzle



Optional Features

50-Hz Motor Stainless Steel Trim Portability Kit Electrical Disconnect Float Tank Automatic Shut Down Timer Remote Station Operation Trigger Activated Start

Trigger Activated Start
Pressure Gauge
Hour Meter
Select 50', 75' or 100' High Pressure Discharge Hose
Hose Reel
Nozzle Sets

Specifications

Turbo Nozzle

Volume - GPM (LPM) 3 (11.4)
Pressure - PSI (BAR) 1000 (69)
BTU Minimum Supply 280000
Exhaust Diameter - Inch (mm) 8 (203.2)
Electric Motor - HP (KW) 2 (1.5)

Dimensions, Inches (cm) 45 (114.3) L X 26 (66) W X 51 (129.5) H

Weight, Lbs (kg) 490 (222)

Standard

| Volts (60Hz) | 120V-1P |
|--------------|---------|
| Amps (60Hz) | 19 |

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



