

Hydroblaster Pressure Washer

3.5/3000 G - Engine Driven, Cold Water Pressure Washer

Hydroblaster 3.5/3000G engine-driven, high-pressure cold water systems provide flow of 3.5-gpm with variable pressure up to 3000-psi. Hydroblaster G system design and quality manufacturing ensures continued performance, reliability and safety. All G model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Formed Steel Base W/ Forklift Slots
- Full Steel Cage Protection
- 1.8 Gallon Fuel Tank
- Direct Driven Pump
- Trigger Gun
- Variable Pressure Wand
- Downstream Chemical Injection
- 50' (15M) High Pressure Discharge Hose
- 15-Degree Nozzle
- Portability Kit - Casters

Optional Features

- Battery - Lead Acid
- Battery - Spiral Cell
- Pressure Gauge
- Hour Meter
- Nozzle Sets
- [Turbo Nozzle](#)
- Hose Reel
- Discharge Hose Lengths



Specifications

Volume - GPM (LPM)	3.5 (13)
Pressure - PSI (BAR)	3000 (207)
Gasoline Engine - HP	13
Dimensions, Inches (mm)	38
Weight, Lbs (kg)	370 (168)

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)