

Hydroblaster Pressure Washer

4/2000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 4/2000E high-pressure cold water systems provide flow of 4GPM with variable pressure up to 2000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776. CSA. and conform to CE standards.

Standard Features

208/230 Volt Fully Hinged Equipment Enclosure Belt Driven Pump Variable Pressure Wand Trigger Gun 15-Degree Nozzle



50-Hz Motor

Stainless Steel Covers
Electrical Disconnect
Float Tank
Automatic Shut Down Timer
Remote Station Operation
Trigger Activated Start
Pressure Gauge
Hour Meter
Non Marking, Discharge Hose
Hose Reel
Nozzle Sets

Specifications

Turbo Nozzle

 Volume - GPM (LPM)
 4 (15.4)

 Pressure - PSI (BAR)
 2000 (138)

 Electric Motor - HP (KW)
 5 (3.73)

Dimensions, Inches (cm) 32 (81.3) L X 25 (63.5) W X 39 (99) H

Weight, Lbs (kg) 420 (191)

Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P	
Amps (60Hz)	25	14	7	



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



