

Hydroblaster Pressure Washer

4/2000 EE - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/2000EE high-pressure hot water systems provide flow of 4 GPM with variable pressure up to 2000 PSI. All EE systems are electrically heated systems designed for use in environmentally sensitive areas and do not have an open flame. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EE model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards and heating modules are CSA approved.

Standard Features

208/230 Volt
Full Equipment Covers
Belt Driven Pump
Low Heater Solution Shut Down
Variable Pressure Trigger Wand
15-Degree Nozzle

Optional Features

50-Hz Motor
Stainless Steel Covers
Electrical Disconnect
Automatic Shut Down Timer
[Remote Station Operation](#)
Trigger Activated Start
Pressure Gauge
Hour Meter
[High Pressure Soap/Chemical Injection](#)
Select 50', 75', or 100' High Pressure Discharge Hose
Hose Reel
Nozzle Sets
[Turbo Nozzle](#)



Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
Electric Heating System - KW	48
Electric Motor - HP (KW)	5 (3.7)
Dimensions, Inches (cm)	32 (81.3) L X 32 (81.3) W X 50 (126) H
Weight, Lbs (kg)	510 (231)

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	140	65

Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)