

Hydroblaster Pressure Washer

4/2000 SSOV - Portable Space Saving Design, Electric Driven, Oil Heated

Featuring a portable, space saving design, the Hydroblaster 4/2000SSOV high-pressure hot water systems provide flow of 4 GPM with variable pressure up to 2000 PSI. All SSOV systems can be configured to be heated by multiple types of oil, including kerosene, diesel, and JP fuels. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All SSOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- Portable Space Saving Design
- Control Panel
- Schedule 80 Coil Warranty
- Automatic Ignition
- 6 Gallon Fuel Oil Tank
- 8 Gallon Engine Fuel Tank
- Direct Drive Pump
- Nozzle
- Trigger Gun
- Variable Pressure Wand
- Downstream Chemical Injection
- 50' (15M) High Pressure Discharge Hose
- 15-Degree Nozzle



Optional Features

- Stainless Steel Trim
- Adjustable Thermostat
- Pressure Gauge
- Hour Meter
- Nozzle Sets
- [Turbo Nozzle](#)
- Machine Mounted Hose Reel
- Discharge Hose Lengths

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	2000 (138)
BTU Minimum Supply	360,000
Exhaust Diameter - Inch (mm)	8" (203)
Electric Motor - HP (KW)	5 (3.7)
Dimensions, Inches (cm)	45" (114.3) L X 26" (66) W X 56" (142.2) H
Weight, Lbs (kg)	550 (249)

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)



Hydroblaster Pressure Washer

4/2000 SSOV - Portable Space Saving Design, Electric Driven, Oil Heated

	Standard		
Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	23	14	7

Pricing

For complete pricing details,
Submit a quote online below.

[Get a Quote](#)

