Hydroblaster Pressure Washer

4/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/3000EHOV high-pressure hot water systems provide flow of 4GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Hinged Access Equipment Enclosure
Premium Efficiency Drive Motor
Belt Driven Pump
Schedule 80 Coil With Extended Warranty
Automatic System Shutdown Timer
Automatic Burner Ignition and Controls
6 Gallon Front Fill Fuel Oil Tank
Low Fuel Level Burner Lockout w/ Indicator
Trigger Gun System Discharge Control
Dual Nozzle Variable Pressure Wand

Optional Features

Suitable For a Variety of Power Supplies Including 50Hz
Lockable Power Disconnect Switch
Hour Meter, Pressure and Temperature Gauges
Trigger Actuated Start
Remote Control Station In NEMA 4X Enclosures
Stainless Trim; Pump Enclosure and Coil Housing
Nozzle Options including Turbo Nozzle
Discharge Soap/Chemical Injection
Precision (Peristaltic Pump) Inlet Soap
Soap Injection Flow Meter
Plastic Float Tank
Fresh/Recycle Water Supply w/Motorized Ball Valve
Hose Reels
HP Hose, Various Lengths

Pricing

For complete pricing details,
Submit a quote online below.

Get a Quote

Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering, Inc. 2024

Hydroblaster Pressure Washer

4/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

Volume - GPM (LPM)	4 (15.4)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	360000
Exhaust Diameter - Inch (mm)	8 (203.2)
Electric Motor - HP (KW)	7.5 (5.59)
Dimensions, Inches (cm)	42.25 (115) L X 31.75 (80.6) W X 55 (139.7) H
Weight, Lbs (kg)	718 (326)
Frame	5BK169 (Sm.)
Coil	18"
Burner	HD-201PC
SS Trim - Height	53 7/8"

	Standard		
Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	33	22	11

Pricing

For complete pricing details,
Submit a quote online below.

Get a Quote

Copyright Hydro Engineering, Inc. 2024