

# **Hydroblaster Pressure Washer**

#### 4/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/3000EHOV high-pressure hot water systems provide flow of 4GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

#### **Standard Features**

208/230 Volt

Hinged Access Equipment Enclosure Premium Efficiency Drive Motor

Belt Driven Pump

Schedule 80 Coil With Extended Warranty

Automatic System Shutdown Timer

Automatic Burner Ignition and Controls

6 Gallon Front Fill Fuel Oil Tank

Trigger Gun System Discharge Control Dual Nozzle Variable Pressure Wand

Discharge Soap/Chemical Injection



#### **Optional Features**

Suitable For a Variety of Power Supplies Including 50Hz

Lockable Power Disconnect Switch

Hour Meter, Pressure and Temperature Gauges

**Trigger Actuated Start** 

Remote Control Station In NEMA 4X Enclosures

Stainless Trim; Pump Enclosure and Coil Housing

Nozzle Options including Turbo

Plastic Float Tank

Fresh/Recycle Water Supply w/Motorized Ball Valve

Hose Reels

HP Hose, Various Lengths

## **Specifications**

 Volume - GPM (LPM)
 4 (15.4)

 Pressure - PSI (BAR)
 3000 (207)

 BTU Minimum Supply
 360000

 Exhaust Diameter - Inch (mm) 8 (203.2)

 Electric Motor - HP (KW)
 7.5 (5.59)

Dimensions, Inches (cm) 42.25 (115) L X 31.75 (80.6) W X 55 (139.7) H

Weight, Lbs (kg) 718 (326) Frame 5BK169 (Sm.)

Coil 18"

Burner HD-201PC SS Trim - Height 53 7/8"

#### Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P	
Amps (60Hz)	33	22	11	

### Pricing

For complete pricing details, Submit a quote online below.

**Get a Quote** 



