

# Hydroblaster Pressure Washer

## 4/4000 EE - Electric Motor, Hot Water Pressure Washer

Hydroblaster 4/4000EE high-pressure hot water systems provide flow of 4 GPM with variable pressure up to 4000 PSI. All EE systems are electrically heated systems designed for use in environmentally sensitive areas and do not have an open flame. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EE model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards and heating modules are CSA approved.

### Standard Features

- Full Equipment Covers
- Belt Driven Pump
- Auto Start With Trigger Pull
- Time Delayed System Shutdown
- Stainless Steel Coil
- Low Heater Solution Shut Down
- No Direct Immersion Heating Elements Eliminate Scale Buildup
- Temperature Control
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 50' (15M) High Pressure Discharge Hose
- 15-Degree Nozzle



### Optional Features

- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Pressure Gauge
- Temperature Gauge
- Thermostat
- [High Pressure Soap/Chemical Injection](#)
- Longer Hose Lengths
- Hose Reel
- Nozzle Sets
- [Turbo Nozzle](#)

### Pricing

For complete pricing details,  
Submit a quote online below.

[Get a Quote](#)



# Hydroblaster Pressure Washer

## 4/4000 EE - Electric Motor, Hot Water Pressure Washer

### Specifications

Volume - GPM (LPM) 4 (15.4)  
 Pressure - PSI (BAR) 4000 (276)  
 Electric Heating System - KW 48  
 Electric Motor - HP (KW) 10 (7.46)  
 Dimensions, Inches (cm) 32" (81.3) L X 24" (60.9) W X 50" (126) H  
 Weight, Lbs (kg) 565 (256)

	Standard	
<b>Volts (60Hz)</b>	230V-3P	460V-3P
<b>Amps (60Hz)</b>	154	71

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

