

Hydroblaster Pressure Washer

5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/1500EHOV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 1500PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

208/230 Volt
Hinged Access Equipment Enclosure
Premium Efficiency Drive Motor
Belt Driven Pump
Schedule 80 Coil With Extended Warranty
Automatic System Shutdown Timer
Automatic Burner Ignition and Controls
6 Gallon Front Fill Fuel Oil Tank
Trigger Gun System Discharge Control
Dual Nozzle Variable Pressure Wand
Discharge Soap/Chemical Injection
Hour Meter



Suitable For a Variety of Power Supplies Including 50Hz
Lockable Power Disconnect Switch
Pressure and Temperature Gauges
Trigger Actuated Start
Remote Control Station In NEMA 4X Enclosures
Stainless Trim; Pump Enclosure and Coil Housing
Nozzle Options including Turbo Nozzle
Plastic Float Tank
Fresh/Recycle Water Supply w/Motorized Ball Valve
Hose Reels
HP Hose, Various Lengths



Pricing

For complete pricing details, Submit a quote online below.

Get a Quote







Hydroblaster Pressure Washer

5/1500 EHOV - Electric Motor, Hot Water Pressure Washer

Specifications

 Volume - GPM (LPM)
 5 (18.9)

 Pressure - PSI (BAR)
 1500 (103)

 BTU Minimum Supply
 440000

 Exhaust Diameter - Inch (mm) 8 (203.2)

 Electric Motor - HP (KW)
 5 (3.73)

Dimensions, Inches (cm) 42.25 (115) L X 31.75 (80.6) W X 50 (127) H

Weight, Lbs (kg) 688 (312) Frame 5BK169 (Sm.)

Coil 18"

Burner HD-201PC SS Trim - Height 53 7/8"

Standard

Volts (60Hz)	230V-1P	230V-3P	460V-3P
Amps (60Hz)	23	14	7

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



