

Hydroblaster Pressure Washer

5/2000 EHG - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/2000EHGV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 2000PSI. All EHG systems can be configured for natural gas or propane heating operation. Systems employ high efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHG model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- 208/230 Volt
- Hinged Access Equipment Enclosure
- Premium Efficiency Drive Motor
- Belt Driven Pump
- Schedule 80 Coil With Extended Warranty
- Draft Diverter
- Automatic System Shut Down Timer
- Automatic Burner Ignition and Controls
- Trigger Gun System Discharge Control
- Discharge Soap/Chemical Injection
- Dual Nozzle Variable Pressure Wand



Optional Features

- Suitable For a Variety of Power Supplies Including 50Hz
- Power Vent Burner Exhaust
- Lockable Power Disconnect Switch
- Hour Meter, Pressure and Temperature Gauges
- Trigger Actuated Start
- Remote Control Station In NEMA 4X Enclosures
- Stainless Trim: Pump Enclosure and Coil Housing
- Nozzle Options including Turbo Nozzle
- Plastic Float Tank
- Fresh/Recycle Water Supply w/Motorized Ball Valve
- Hose Reels
- HP Hose, Various Lengths

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	2000 (138)
BTU Minimum Supply	400000
Exhaust Diameter - Inch (mm)	10 (254)
Electric Motor - HP (KW)	7.5 (5.59)
Dimensions, Inches (cm)	45.25 (115) L X 31.75 (80.6) W X 55 (139.7) H
Weight, Lbs (kg)	710 (322)
Frame	5BK169 (Sm.)
Coil	20"
Burner	X44

Standard

Volts (60Hz)	230V-1p	230V-3P	460V-3P
Amps (60Hz)	33	22	11

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)