

# Hydroblaster Pressure Washer

## 5/3000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 5/3000E high-pressure cold water systems provide flow of 5GPM with variable pressure up to 3000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

### Standard Features

- 208/230 Volt
- Fully Hinged Equipment Enclosure
- Belt Driven Pump
- Variable Pressure Wand
- Trigger Gun
- 15-Degree Nozzle

### Optional Features

- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Float Tank
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Pressure Gauge
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50' or 100' High Pressure, Non Marking, Discharge Hose
- Hose Reel
- Nozzle Sets
- [Turbo Nozzle](#)



### Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	32 (81.3) L X 25 (63.5) W X 39 (99) H
Weight, Lbs (kg)	445 (202)

	Standard	
Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	25	13

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)