

# **Hydroblaster Pressure Washer**

5/3000 E - Electric Motor, Cold Water Pressure Washer

Hydroblaster 5/3000E high-pressure cold water systems provide flow of 5GPM with variable pressure up to 3000PSI. Systems employ high efficiency motors compatible with any electrical supply voltage for both 60Hz or 50Hz operation. All E model Hydroblaster pressure washers are certified to UL-1776. CSA. and conform to CE standards.

### **Standard Features**

208/230 Volt
Fully Hinged Equipment Enclosure
Belt Driven Pump
Variable Pressure Wand
Trigger Gun
15-Degree Nozzle
Hour Meter



### **Optional Features**

50-Hz Motor Stainless Steel Covers Electrical Disconnect Float Tank Automatic Shut Down Timer Remote Station Operation

Automatic Shut Down Timer
Remote Station Operation
Trigger Activated Start
Pressure Gauge
Select 50' or 100' High Pressure, Non Marking, Discharge Hose
Hose Reel
Nozzle Sets
Turbo Nozzle

## **Specifications**

 Volume - GPM (LPM)
 5 (18.9)

 Pressure - PSI (BAR)
 3000 (207)

 Electric Motor - HP (KW)
 10 (7.46)

Dimensions, Inches (cm) 32 (81.3) L X 25 (63.5) W X 39 (99) H

Weight, Lbs (kg) 445 (202)

#### Standard

Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	25	13

### **Pricing**

For complete pricing details, Submit a quote online below.

Get a Quote



