

# Hydroblaster Pressure Washer

## 5/3000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/3000EHOV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 3000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

### Standard Features

- Full Equipment Covers
- Belt Driven Pump
- Schedule 80 Coil Warranty
- Automatic Ignition
- 6 Gallon Fuel Oil Tank
- Soap/Chemical Injection
- Variable Pressure Trigger Wand
- 15-Degree Nozzle

### Optional Features

- Fuel - Natural Gas or LP Gas
- 50-Hz Motor
- Stainless Steel Covers
- Electrical Disconnect
- Power Vent With Controller
- Automatic Shut Down Timer
- [Remote Station Operation](#)
- Trigger Activated Start
- Steam Combo
- Pressure Gauge
- Precision Thermal Management (PTM)
- Hour Meter
- [High Pressure Soap/Chemical Injection](#)
- Select 50', 75' or 100' High Pressure Discharge Hose
- Hose Reel
- [Turbo Nozzle](#)



### Pricing

For complete pricing details,  
Submit a quote online below.

[Get a Quote](#)



# Hydroblaster Pressure Washer

## 5/3000 EHOV - Electric Motor, Hot Water Pressure Washer

### Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	3000 (207)
BTU Minimum Supply	440,000
Exhaust Diameter - Inch (mm)	10" (254)
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	45" (114.3) L X 33" (83.8) W X 54" (137.2) H
Weight, Lbs (kg)	710 (322)

	Standard	
<b>Volts (60Hz)</b>	230V-3P	460V-3P
<b>Amps (60Hz)</b>	25	13

### Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

