

Hydroblaster Pressure Washer

5/5000 EHOV - Electric Motor, Hot Water Pressure Washer

Hydroblaster 5/5000EHOV high-pressure hot water systems provide flow of 5GPM with variable pressure up to 5000PSI. All EHOV systems can be configured to be heated by a variety of oils, including kerosene, diesel, and JP fuels. Systems employ high-efficiency motors compatible with various electrical supply voltage for either 60Hz or 50Hz operation. All EHOV model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- 208/230 Volt
- Hinged Access Equipment Enclosure
- Premium Efficiency Drive Motor
- Belt Driven Pump
- Schedule 80 Coil With Extended Warranty
- Automatic System Shutdown Timer
- Automatic Burner Ignition and Controls
- 6 Gallon Front Fill Fuel Oil Tank
- Trigger Gun System Discharge Control
- Dual Nozzle Variable Pressure Wand
- Discharge Soap/Chemical Injection



Optional Features

- Suitable For a Variety of Power Supplies Including 50Hz
- Lockable Power Disconnect Switch
- Hour Meter, Pressure and Temperature Gauges
- Trigger Actuated Start
- Remote Control Station In NEMA 4X Enclosures
- Stainless Trim; Pump Enclosure and Coil Housing
- Nozzle Options including Turbo Nozzle
- Plastic Float Tank
- Fresh/Recycle Water Supply w/Motorized Ball Valve
- Hose Reels
- HP Hose, Various Lengths

Specifications

Volume - GPM (LPM)	5 (18.9)
Pressure - PSI (BAR)	5000 (345)
BTU Minimum Supply	440000
Exhaust Diameter - Inch (mm)	8 (203.2)
Electric Motor - HP (KW)	20 (14.9)
Dimensions, Inches (cm)	42.75 (115) L X 31.75 (80.6) W X 50 (127) H
Weight, Lbs (kg)	785 (356)
Frame	5BK169 (Sm.)
Coil	18"
Burner	HD-401PC
SS Trim - Height	53 7/8"

Standard

Volts (60Hz)	230V-3P	460V-3P
Amps (60Hz)	53	27

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)

Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181

Subject to change without notice

Copyright Hydro Engineering, Inc. 2025