

Hydroblaster Pressure Washer

5/5000 GHO - Engine Driven, Skid Mounted Pressure Washer

Hydroblaster 5/5000GHO engine-driven, high-pressure hot water systems provide flow of 5-gpm with variable pressure up to 5000-psi. All GHO systems can be configured for heating operation through various tupes of oil, including kerosene, diesel, and JP fuels. Hydroblaster GHO system design and quality manufacturing ensures continued performance, reliability and safety. All GHO model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

Gasoline Engine Steel Base Plate With Forklift Slots Full Locking Equipment Enclosure Schedule 80 Coil Warranty Control Panel 6 Gallon Fuel Oil Tank 8 Gallon Carb Compliant Engine Fuel Tank Belt Driven Pump Trigger Gun Variable Pressure Wand **Downstream Chemical Injection** 15-Degree Nozzle



Diesel Engine Stainless Steel Enclosure Battery - Lead Acid Battery - Spiral Cell Adjustable Thermostat Temperature Gauge Pressure Gauge Hour Meter Nozzle Sets

Turbo Nozzle

Hose Reel

Discharge Hose Lengths

Steam Combo

Precision Thermal Management (PTM)



Specifications

Volume - GPM (LPM) 5 (18.9) Pressure - PSI (BAR) 5000 (345) **BTU Minimum Supply** 450,000 Gasoline Engine - HP

63" (160) L X 54" (137.1) W X 33" (83.8) H Dimensions, Inches (cm)

Weight, Lbs (kg) 1250 (567)

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



