

Hydroblaster Pressure Washer

5/5000 GHO - Engine Driven, Skid Mounted Pressure Washer

Hydroblaster 5/5000GHO engine-driven, high-pressure hot water systems provide flow of 5-gpm with variable pressure up to 5000-psi. All GHO systems can be configured for heating operation through various tupes of oil, including kerosene, diesel, and JP fuels. Hydroblaster GHO system design and quality manufacturing ensures continued performance, reliability and safety. All GHO model Hydroblaster pressure washers are certified to UL-1776, CSA, and conform to CE standards.

Standard Features

Gasoline Engine
Steel Base Plate With Forklift Slots
Full Locking Equipment Enclosure
Schedule 80 Coil Warranty
Control Panel
6 Gallon Fuel Oil Tank
8 Gallon Engine Fuel Tank
Belt Driven Pump
Trigger Gun
Variable Pressure Wand
Downstream Chemical Injection
15-Degree Nozzle



Optional Features

Diesel Engine
Stainless Steel Enclosure
Battery - Lead Acid
Battery - Spiral Cell
Adjustable Thermostat
Temperature Gauge
Pressure Gauge
Hour Meter
Nozzle Sets
Turbo Nozzle
Hose Reel

Specifications

Discharge Hose Lengths

 Volume - GPM (LPM)
 5 (18.9)

 Pressure - PSI (BAR)
 5000 (345)

 BTU Minimum Supply
 450000

 Gasoline Engine - HP
 25

Dimensions, Inches (cm) 63 (160) L X 54 (137.1) W X 33 (83.8) H

Weight, Lbs (kg) 1250 (567)

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



