

Hydroblaster Pressure Washer

5/5000 GS - Pressure Washer, Engine Driven, Skid Mounted

Hydroblaster 5/5000GS engine-driven, high-pressure cold water systems provide flow of 5-gpm with variable pressure up to 5000-psi. Hydroblaster GS system design and quality manufacturing ensures continued performance, reliability and safety. All GS model Hydroblaster pressure washers are certified to UL-1776. CSA. and conform to CE standards.

Standard Features

Steel Base Plate With Forklift Slots Full Locking Equipment Enclosure 8 Gallon Engine Fuel Tank Belt Driven Pump Trigger Gun Variable Pressure Wand Downstream Chemical Injection 50' (15M) High Pressure Discharge Hose 15-Degree Nozzle



Optional Features

Diesel Engine Stainless Steel Enclosure Battery - Lead Acid Battery - Spiral Cell Pressure Gauge Hour Meter Nozzle Sets Turbo Nozzle Hose Reel

Specifications

Discharge Hose Lengths

Volume - GPM (LPM) Pressure - PSI (BAR) Gasoline Engine - HP Dimensions, Inches (cm) Weight, Lbs (kg) 5 (18.9) 5000 (345) 25 56 (142.2) L X 30 (76.2) W X 33 (83.8) H 795 (361)

Pricing

For complete pricing details, Submit a quote online below.

Get a Quote



Hydro Engineering, Inc. | 865 W 2600 S - Salt Lake City, UT 84119 | 801-972-1181



Subject to change without notice Copyright Hydro Engineering, Inc. 2025