



Wash - Collect - Recycle

Hydro Engineering, Inc.  
865 West 2600 South  
Salt Lake City, Utah 84119  
hydroblaster.com

Hydroblaster™ - Hydropad™ - Hydrokleen™

## Hydro Heater – Natural Gas Fired Heat

MODEL HH-G VOLUME (GPM)	2-4 GPM	5 GPM	6-7 GPM
WEIGHT (LBS)	220		285
DIMENSIONS	20" W X 43" H X 21" L		21" W X 46" H X 21" L

### Standard Features:

- Can be used with most any pressure washer
- Fuel - natural gas
- Requires 110 volt power supply
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls
- Gas regulator is not supplied



Choose your options (STD- designates the standard)

### Temperature Controls

- STD- Thermostat, 225° High Limit, NC
- OPT- Thermostat, Adjustable, 85-250°F

### Electrical: Power & Controls

- STD- 115 Volt, Auto Burner Ignition

### Flow & Trim Options

- STD- 2 GPM, To 4000 PSI, Painted Trim
- OPT- 2 GPM, To 4000 PSI, Stainless Trim
- OPT- 3-4 GPM, To 4000 PSI, Painted Trim
- OPT- 3-4 GPM, To 4000 PSI, Stainless Trim
- OPT- 5 GPM, To 4000 PSI, Painted Trim
- OPT- 5 GPM, To 4000 PSI, Stainless Trim
- OPT- 6-7 GPM, To 4000 PSI, Painted Trim
- OPT- 6-7 GPM, To 4000 PSI, Stainless Trim

### Exhaust Options

- STD- Draft Diverter 8" Flue, Painted Top
- OPT- Draft Diverter 8" Flue, Stainless Top
- OPT- Draft Diverter, 10", Painted Top
- OPT- Draft Diverter, 12" Painted Top
- OPT- Power Vent System, 2-4 gpm
- OPT- Power Vent System, 5 gpm
- OPT- Power Vent System, 6-7gpm

### System Gauge Options

- STD-No Pressure Gauge
- OPT-Pressure Gauge, Pipe Mounted
- OPT-Temperature Gauge

1. Specifications are effective 2016. 2. Specifications are subject to change without notice



Intertek

Certified Systems Available