



Wash - Collect - Recycle

Hydro Engineering, Inc.
865 West 2600 South
Salt Lake City, Utah 84119
hydroblaster.com

Hydroblaster™ - Hydropad™ - Hydrokleen™

Hydro Heater – LP or Natural Gas Fired Heat MODEL HH-G & HH-LP

VOLUME (GPM)	2-4 GPM	5 GPM	6-7 GPM
WEIGHT (LBS)	220	285	
DIMENSIONS	20" W X 43" H X 21" L	21" W X 46" H X 21" L	

Standard Features:

- Can be used with most any pressure washer
- Fuel - natural gas
- Requires 110 volt power supply
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls
- Gas regulator is not supplied



Choose your options (STD- designates the standard)

Part #	Description	Part #	Description
	Temperature Controls		Exhaust Options
1SP592*	High Limit Temperature Switch, 225°F	8DD-1*	Draft Diverter, 8", W/Painted Top
2BY021	Thermostat, Adjustable, 85-250°F	8DD-2	Draft Diverter, 8", W/SS Top
	Electrical: Power & Controls	2AF572	Draft Diverter, 10", 20" Coil Top
2AE560*	115VAC, Auto Ignition	2AI608	Draft Diverter, 12", 24" Coil Top
	Flow & Trim Options	2AI609	Power Vent Sys, 2-4GPM GV, 18" Top
2AF575*	2 GPM, To 4000 PSI, Painted Trim	2AJ610	Power Vent System, 5GPM GV, 20" Top
2AF576	2 GPM, To 4000 PSI, Stainless Trim	1XG802	Power Vent System
2BK883	3-4 GPM, To 4000 PSI, Painted Trim		System Gauge Options
2BK884	3-4 GPM, To 4000 PSI, Stainless Trim	1UF035*	No Pressure Gauge
2AF577	5GPM, To 4000PSI, Painted Trim	1UF036	Pressure Gauge, Pipe Mounted
2AF578	5GPM, To 4000PSI, Stainless Trim	1UF037	Temperature Gauge
2AF579	6-7 GPM, To 4000 PSI, Painted Trim		
2AG580	6-7 GPM, To 4000 PSI, Stainless Trim		

1. Specifications are effective 2015. 2. Specifications are subject to change without notice



Certified Systems Available