



Wash - Collect - Recycle

Hydro Engineering, Inc.  
865 West 2600 South  
Salt Lake City, Utah 84119  
hydroblaster.com

Hydroblaster™ - Hydropad™ - Hydrokleen™

## Hydro Heater – Natural Gas Fired Heat MODEL HH-0

<b>VOLUME (GPM)</b>	<b>2-4 GPM</b>	<b>5 GPM</b>	<b>6-7 GPM</b>
<b>WEIGHT (LBS)</b>	220	285	425
<b>DIMENSIONS</b>	20" W X 43" H X 21" L	21" W X 46" H X 21" L	28"W X 52"H X 28"L

### Standard Features:

- Can be used with most any pressure washer
- Fuel – Diesel #1 or 2, Kerosene, JP4, JP8
- Requires 12 volt or 110 volt power supply
- Pressure controlled burner cycling
- Tough 11 gauge steel frame
- High pressure pop-off safety valve
- Over pressure rupture disc
- High limit temperature controls
- 8 gallon fuel tank



Choose your options (STD- designates the standard)

Part #	Description	Part #	Description
	<b>Temperature Controls</b>		<b>Flow &amp; Trim Options</b>
1SP592*	High Limit Temperature Switch, 225°F	2AC546*	2 GPM, To 4000 PSI, Painted Trim
2BY021	Thermostat, Adjustable, 85-250°F	2AC547	2 GPM, To 4000 PSI, Stainless Trim
	<b>Electrical: Power &amp; Controls</b>	2AC548	4-5 GPM, To 4000 PSI, Painted Trim
2AC544*	12 Volt DC, 2 GPM	2AC549	4-5 GPM, To 4000 PSI, Stainless Trim
2AD554	12 Volt DC, 3.5 GPM	2AD550	6-7 GPM, To 4000 PSI, Painted Trim
2AH598	12 Volt DC, 4-5 GPM	2AD551	6-7 GPM, To 4000 PSI, Stainless Trim
2AH599	115 Volt AC, 2 GPM		<b>Frame Options</b>
2EH634	115 Volt AC, 2 GPM, Portable	2AI602*	Stationary, 18"
2AI600	115 Volt AC, 3 GPM	2AI605	Stationary, 20"
2EH635	115 Volt AC, 3 GPM, Portable	2AD558	2-5GPM, Portability Tilt Back, 18"
2AC545	115 Volt AC, 4-5 GPM		<b>System Gauge Options</b>
2EH636	115 Volt AC, 4-5 GPM, Portable	1UF035*	No Pressure Gauge
2EH636	230VAC, 4-5GPM	1UF036	Pressure Gauge, Pipe Mounted
2AD555	115 Volt AC, 6-7 GPM	1UF037	Temperature Gauge

1. Specifications are effective 2015. 2. Specifications are subject to change without notice



Intertek

Certified Systems Available