

Hydroblaster Tandem Axle Trailer

Model TT325

Factory engineered trailers integrate Hydroblaster pressure washers, water tanks, chemical tanks, hose reels and tool boxes into a total portable pressure washer design. All installed optioned equipment and fluid tanks are securely fastened to metal frame members rather than wood decking. Lockable equipment enclosures are typically provided to secure major components.



525 gallon tank shown and adjustable lunette eye hitch

These are not utility trailers

Standard Features:

- 3", 4", & 6" channel iron construction
- Extended A-frame coupler with 2" ball hitch
- Heavy duty jack with 2,000 lb wheel
- 13" wheels and tires
- Electric brakes
- Safety brake actuator
- Dual safety chains
- 12 Volt, D.O.T. approved light package
- 325 gallon water tank

Optional Features:

- 24 Volt D.O.T. approved light package
- 2 5/16" ball hitch
- Adjustable height lunette eye hitch
- 15" wheels and tires
- Spare wheel and tire, trailer mounted
- 2' trailer extension
- Pre-spray soap system
- 30 gallon soap tank
- Hose reel, pre-spray soap system
- Hose reel, inlet water hose
- Pre-spray soap hose, 50' or 100'
- Inlet water hose, 50' or 100'

[Get a Quote](#)

1. Specifications are effective 2018. 2. Specifications are subject to change without notice